Ligen3

A NEW ERA OF LIGHTING



Tried · Trusted · True

Ready to upgrade your lighting game? Discover the power of LEDgen3 and transform your projects now!



Tried · Trusted · True

Embrace the legacy of **Lighting Legends**, pioneering innovation and engineering excellence **since 1926**.



ILLUMINATE YOUR WORLD

WITH UNMATCHED EFFICIENCY & RELIABILITY

Discover Allanson's game-changing **NEW LEDgen3 range**, presenting a diverse array of premium LED module solutions. Immerse yourself in the brilliance of energy-efficient lighting that you can rely on. Engineered to deliver peak performance, our LEDgen3 modules offer unparalleled sustainability while providing radiant light with minimal power usage.

Designed for resilience, our CSA and cULus certified outdoor premium series modules ensure dependable operation even in the toughest weather conditions. Ideal for creating captivating architectural lighting and signage, our LED modules offer effortless peel-and-stick or screw installation, ensuring swift and hassle-free setup.











- Dependable **energy-efficient** illuminations
- IP65 IP68 options available for various environmental conditions
- 12V/24V LEDs for flexible voltage needs
- Operating temperature: -40°C to 60°C
- Delivering hotspot-free, uniform illumination from wide expanses to compact areas
- Recommended depths range from 1.1"- 9.8"
- Built to last and easy to install

Model	Voltage	lm/watt	IP
RGB Addressable LED Module	12V	-	IP67
RGBW LED Module	12V	-	IP66
0.72W LED Module	12V	125	IP65
0.72W Red LED Module	12V	170	IP67
0.72W Orange LED Module	12V	170	IP67
0.72W LED Module	12V/24V	170	IP67
1.4W LED Module	24V	170	IP68
1.08W LED Module	12V	170	IP68
0.72W LED Module	12V/24V	170	IP68
0.36W Micro LED Module	12V/24V	150	IP65



EDgen3

MODULE GUIDE

Tailored Brilliance for Any Signage Depth: Elevate your signage with LEDgen3's precision-engineered modules, meticulously crafted to suit signage of all depths. Illuminate your brand with unrivaled clarity and depth, showcasing your identity in its best light, regardless of scale.





L307W3RGB12A

RGB Addressable LED Module (12V)

- Color: Red, Green, and Blue
- 2.5 Modules/Foot
- 165° Beam Angle
- **IP67 Rated**
- 5 yrs Warranty

Rec. Depth: 1.5" - 6"



L307W3RGBW12 **RGBW LED** Module (12V)

- Color: Red. Green. Blue, and White (7000K)
- 2.5 Modules/Foot 120° Beam Angle
- **IP66 Rated**
- 5 vrs Warranty

Rec. Depth: 4" - 6"



L304W1TWXXM

0.36W Micro LED Module (12V/24V)

- Color/Temperature: 7000K
- 6 Modules/Foot
- 54 Lm/Module
- Efficiency 150 Lm/W 168° x 147° Beam Angle
- IP65 Rated
- 5 yrs Warranty

Rec. Depth: 1.1" - 3.1"



L307W2TWXXP

0.72W LED Module (12V/24V)

- Color/Temperature: 7000K 1.7 Modules/Foot
- 122 Lm/Module
- High efficiency 170 Lm/W
- 170° Beam Angle
- **IP68 Rated**
- 7 yrs Warranty

Rec. Depth: 2" - 6"



L307W2TW12G

0.72W LED Module (12V)

- Color/Temperature: 7000K
- 2 Modules/Foot
- 90 Lm/Module
- Efficiency 125 Lm/W
- 165° Beam Angle 3 yrs Warranty
- IP65 Rated
 - Rec. Depth: 2" 6"



L311W3TW12P

1.08W LED Module (12V)

- Color/Temperature: 7000K
- 1.5 Modules/Foot
- 183.6 Lm/Module
- High efficiency 170 Lm/W
- 170° Beam Angle
- IP68 Rated
- 7 yrs Warranty

Rec. Depth: 3" - 7"



L307W2XXXXB

0.72W LED Module (12V/24V)

- Color/Temperature: 7000K (12V/24V), 5000K(12V), and 3000K (12V)
- 2 Modules/Foot
- 122 Lm/Module
- High efficiency 170 Lm/W
- 170° Beam Angle
- **IP67 Rated**
- 5 vrs Warranty

Rec. Depth: 2" - 9.8"



L314W4TW24P **1.4W LED** Module (24V)

- Color/Temperature: 7000K
- 1.2 Modules/Foot
- 244.8 Lm/Module
- High efficiency 170 Lm/W
- 170° Beam Angle
- **IP68 Rated**
- 7 yrs Warranty

Rec. Depth: 4" - 8"



EDgen3

COLOR MODULES

Vivid Color, Seamless Design: Our LEDgen3 Red and Orange modules deliver vibrant, uniform lighting for any signage depth, combining energy efficiency with striking brilliance. Ensuring bold and lasting impact for your lighting projects.

Dynamic Color Made Easy



L307W2RD12B 0.72W LED Module (12V)

- Color: Red
- 2 Modules/Foot
- 29 Lm/Module
- 41 Lm/W
- 170° Beam Angle
- IP67 Rated
 Five Wessenty
- 5 yrs Warranty

Rec. Depth: 2" - 7.8"



L307W2OR12B **0.72W LED Module (12V)**

- Color: Orange
- 2 Modules/Foot
- 27 Lm/Module
- 37 Lm/W
- 170° Beam Angle
- IP67 Rated
- 5 yrs Warranty

Rec. Depth: 2" - 7.8"







Lighting Evolution Starts Here

Allanson's latest innovations in Colormix lighting: the **RGBW LED Module** and the **RGB Addressable LED Module.** These LEDgendary modules offer stunning color dynamics and individually addressable lighting effects. Designed for versatility, they are perfect for enhancing architectural features, signs, channel letters, and more! With customizable programming, these modules provide tailored lighting solutions to meet any and all demands, ensuring clear and reliable performance for any project. Elevate your lighting with these dynamic RGB lighting solutions.









RGBW LED Module (12V)

L307W3RGBW12





Red, Green, Blue, White (7000K)





2.5 Modules/Foot





120° wide beam angle



0.96W Power Consumption

RGB Addressable LED Module (12V)

L307W3RGB12A


















165° wide beam angle



0.6W Power Consumption



Choosing the Ideal LED Module for your Project



Ideal Module: Thin Depth

0.36W Micro LED Module (12V/24V)





With its compact design, this module delivers powerful brightness, **ideal for tight spaces** without compromising lighting quality.

Ideal Module: Medium Depth

0.72W LED Module (12V/24V)





Despite its small size, this impressive LED provides ample brightness to illuminate medium-depth spaces efficiently and reliably.

Ideal Module: Thick Depth

0.72W LED
Module (12V/24V)





Our most versatile LED illuminates signage from 2" to a significant 9.8" depth. Engineered for peak performance at any depth.

























Module	
Co	
LED/Modi	
Module	
Beam Anı	7°
Watta	
Input Volta	V
Operat Temperature ()°C
IP Rati	
Recommend Dep	,
\A/	

Module #	L307W3RGBW12	L307W3RGB12A		
Color	Red, Green, Blue, and White (7000K)	Red, Green, Blue		
.ED/Module	3	3		
Module/Ft	2.5	2.5		
Beam Angle	120°	165°		
Wattage	0.96W	0.6W		
put Voltage	12V	12V		
Operating nperature (°C)	-40°C ~ 60°C	-40°C ~ 60°C		
IP Rating	IP66	IP67		
ommended: Depth	4"-6"	1.5"-6"		
Warranty	5 yrs	5 yrs		

Module #	L314W4TW24P	L311W3TW12P	L307W2TWXXP	L307W2XXXXB	L307W2RD12B	L307W20R12B	L307W2TW12G	L304WITWXXM
Color	7000K	7000K	7000K	7000K, 5000K, 3000K	Red	Orange	7000K	7000K
LED/Module	4	3	2	2	2	2	2	1
Module/Ft	1.2	1.5	1.7	2	2	2	2	6
Lm/Module	244.8	183.6	122	122	29	27	90	54
Lm/Ft	293.8	275.4	207	244	58	54	180	324
Lm/Watt	170	170	170	170	41	37	125	150
Beam Angle	170°	170°	170°	170°	170°	170°	165°	168° x 147°
Wattage	1.44W	1.08W	0.72W	0.72W	0.72W	0.72W	0.72W	0.36W
Input Voltage	24V	12V	12V & 24V	12V & 24V(7000K)	12V	12V	12V	12V & 24V
Operating Temperature (°C)	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C	-40°C ~ 60°C
IP Rating	IP68	IP68	IP68	IP67	IP67	IP67	IP65	IP65
Recommended Depth	4"-8"	3"-7"	2"-6"	2"-9.8"	2"-7.8"	2"-7.8"	2"-6"	1.1"-3.1"
Warranty	7 yrs	7 yrs	7 yrs	5 yrs	5 yrs	5 yrs	3 yrs	5 yrs





Allanson

Tried · Trusted · True

cservice@allanson.com | 1.800.661.7251 | www.allanson.com

