

Row Spacing Guide - Using LEDgen3 0.72W Modules (12V or 24V)

WHITE B MODULES

COLOR B MODULES

WHITE G MODULES

WHITE P MODULES

PART NUMBER	L307W2WWXXB L307W2NWXXB L307W2TWXXB		L307W2RD12B L307W2OR12B		L307W2TW12G		L307W2TWXXP	
	Sign Depth (inch)	Mod / ft	Row Spacing (inch)	Mods / ft	Row Spacing (inch)	Mods / ft	Row Spacing (inch)	Mods / ft
2	2	4 to 5	2	4 to 5	4	3	-	-
3	-	-	-	-	3	4	1.7	7
4	2	8 to 9.5	2	8 to 9.5	2	6	1.7	10
5	-	-	-	-	2	9	1.7	14
6	2	13 to 14	2	13 to 14	2	12	1.7	15
7	-	-	-	-	-	-	-	-
8	2	15 to 16	2	15 to 16	-	-	-	-

Note: This is only a guide. Results may vary by sign manufacturer. Testing is recommended.

Tested Sign Face: 3/16" Polycarbonate
Test Conditions: Single-sided box, thin layer of flat white primer inside, no internal structures.
Diffusers Used: None
Test Date: February / September 2025

